



## New! XENYX Premium Mic/Line Mixers with USB, One-Knob Compressors and Massive Software Bundle

Our new XENYX USB Series mixers are designed to handle your live gigs, as well as provide all the state-of-the-art tools you will need to make stunning, professional-quality recordings. Our built-in, hassle-free USB/Audio Interfaces provide the ultimate in personal computer connectivity. In addition to onboard USB/Audio Interfaces, these mixers feature premium XENYX mic preamps, studio-grade "one-knob" compressors (on all mono channels), and recording and editing software that will turn your computer system into a complete, high-performance home recording studio. Channel EQ is provided by our highly musical "British" 3-band EQs, which deliver the same sonic performance as the mega-consoles of the '60s and '70s. Now you can make a little music history of your own—with the new XENYX USB series mixers!

### Common features:

- Premium ultra-low noise, high headroom analog mixer
- State-of-the-art XENYX Mic Preamps comparable to stand-alone boutique preamps
- Studio-grade compressors with super-easy "one-knob" functionality on all mono channels
- Neo-classic "British" 3-band EQs for warm and musical sound
- New studio-grade FX processor with 16 editable presets including reverb, chorus, flanger, delay, pitch shifter, multi-effects, Tap function and storable user parameter settings (not available on 1204USB)
- Built-in stereo USB/Audio Interface to connect directly to your computer
- Free audio recording, editing and podcasting software plus 150 instrument/effect plug-ins and ultra-low latency driver included
- Revolutionary energyXT2.5 Compact BEHRINGER Edition music production software included with feature-rich audio/MIDI sequencer that loads almost instantaneously on all computer platforms
- Channel inserts on each mono channel for flexible connection of outboard equipment (not available on 1204USB or X1204USB)
- 2-4 aux sends per channel (see table for details)
- Clip LEDs on all channels
- 2-4 multi-functional stereo aux returns for flexible routing (see table for details)
- Balanced main mix outputs with gold-plated XLR connectors
- Control room/phones outputs with multi-input source matrix
- Long-wearing 60-mm logarithmic-taper faders and sealed rotary controls
- "Planet Earth" switching power supply for maximum flexibility (100 - 240 V~), noise-free audio, superior transient response plus low power consumption for energy saving
- Rack mount brackets included for ultimate flexibility



Massive software bundle includes energyXT2.5 Compact BEHRINGER Edition, 100 virtual instruments, more than 50 VST effects plus an unlimited number of sound creations. Compatible with Windows XP, Windows Vista, Mac OS X and Linux operating systems.

	X2442USB	X2222USB	X1832USB	X1622USB	X1222USB	X1204USB	1204USB
Total inputs	24	22	18	16	16	12	12
Mono/stereo input channels	8/4	8/4	6/4	4/4	4/4	4/2	4/2
Mix Buses	4/2	2/2	3/2	2/2	2/2	2/2	2/2
XENYX Mic preamps	10	8	6	4	6	4	4
Mono Channel EQ	3-band	3-band	3-band	3-band	3-band	3-band	3-band
Channel effects sends MON/FX	2/2	1/2	1/2	1/1	1/1	1/1	0/2
Effects returns	4 stereo	3 stereo	2 stereo	2 stereo	2 stereo	2 stereo	2 stereo
USB output/interface	2-in/2-out	2-in/2-out	2-in/2-out	2-in/2-out	2-in/2-out	2-in/2-out	2-in/2-out
FX processor presets	16	16	16	16	16	16	—
Metering	12-LED	12-LED	12-LED	12-LED	12-LED	8-LED	12-LED
Weight	13 lbs/5.9 kg	10.5 lbs/4.7 kg	10.2 lbs/4.6 kg	7.6 lbs/3.4 kg	8.1 lbs/3.7 kg	6.2 lbs/2.8 kg	6.2 lbs/2.8 kg
Other features	Sweepable mids on mono channels, 4-band fixed EQ on stereo channels, +48 V phantom power, four subgroups	Sweepable mids on mono channels, 4-band fixed EQ on stereo channels, +48 V phantom power, two subgroups	Sweepable mids on mono channels, 4-band fixed EQ on stereo channels, 9-band graphic EQ, Voice Canceller, FBQ Feedback Detection System, XPO 3-D stereo surround, +48 V phantom power	Sweepable mids on mono channels, 4-band fixed EQ on stereo channels, +48 V phantom power	7-band graphic EQ, Voice Canceller, FBQ Feedback Detection System, XPO 3-D stereo surround, +48 V phantom power	Mute/Air 3-4 bus, multi-input source matrix, +48 V phantom power	Mute/Air 3-4 bus, multi-input source matrix, +48 V phantom power